



### SSG030NVEPXS1YL000 2×30 lb (14 kg)

### ROI...Reimagined

Speed Queen's stacked washer-extractor/tumble dryer, featuring the Quantum Touch control, is a unique product that truly delivers return on investment.

- Designed to produce maximum ROI per square foot for laundries where space is at a premium
- Offers all the benefits of a Speed Queen 30-pound washer-extractor and tumbler dryer (50-pound version also available)
- A flush-mounted soap dispenser contributes to the machine's sleek, modern design, that includes stainless steel with chrome accents
- Minimal front fasteners gives quick access to key washer-extractor components to improve serviceability
- Tumble dryer features two cycle modifiers for additional profit potential
- Great product for owners to differentiate their store from the competition. The stack provides customers an all-in-one option, with no need to use a laundry cart to transfer loads across the store to the tumble dryer section.





## Stacked Washer-Extractor/Tumble Dryers

#### Quantum® Touch Control

Reimagine your laundry experience with the Speed Queen Quantum Touch display. Clear, easy to use, easy to understand directions with profitable cycle modifiers enhance your customers' experience and increase return on investment.

- User-friendly screens with operating instructions built in as part of the control
- Washer-Extractor:
  15 total cycle options, 3 basic cycles, 1 custom cycle, 3 basic temperature options
- Tumble Dryer:
  5 basic cycles (high, medium, low, delicate, no heat)
- Easy-to-understand cycle modifier prompts will encourage your customers to customize their dry
- Flexible pricing & additional revenue opportunities with customizable cycle modifiers, time-of-day pricing and lucky cycle options
- 30+ languages available
- On-screen timer so your customers know exactly how much time their cycle will take
- · Speed Cycle option for those who want to get in and out quickly
- · Flexible Payment Options Coin, Card, Mobile, Cash











SPEED QUEEN® INSIGHTS READY

Take your business to new levels of efficiency and profitability with advanced analytics and customer data—all integrated into the same

platform with the rest of your business management tools. Know how often each customer visits, which machines they use, how they pay, and use that information to increase your revenue through stronger customer relationships and a more rewarding laundry experience.

# Stacked Washer-Extractor/Tumble Dryers

|                                              | SSG030NVEPXS1YL000            |                      |  |
|----------------------------------------------|-------------------------------|----------------------|--|
|                                              | Washer-Extractor              | Tumble Dryer         |  |
| Control Option                               | Qua                           | Quantum Touch        |  |
| Capacity - lb (kg)                           | 3                             | 30 (13) x 2          |  |
| Overall Width - in (mm)                      |                               | 31.4 (797)           |  |
| Overall Depth - in (mm)                      |                               | 45.5 (1152)          |  |
| Overall Height - in (mm)                     | 7                             | 79.7 (2023)          |  |
| Cylinder Diameter - in (mm)                  | 24.0 (610)                    | 30.0 (762)           |  |
| Cylinder Depth - in (mm)                     | 16.0 (406)                    | 26.0 (660)           |  |
| Cylinder Volume - cu. ft (liters)            | 4.2 (119)                     | 10.6 (300)           |  |
| Reversing Cylinder                           | -                             | Standard             |  |
| Door Opening Size - in (mm)                  | 14.3 (363)                    | 22.6 (574)           |  |
| Door Bottom to Floor - in (mm)               | 14.0 (356)                    | 51.3 (1303)          |  |
| Water Inlet Connection - in (mm)             | 2 × 0.75 (19)                 | -                    |  |
| Drain Diameter - in (mm)                     | 1 x 3 (76)                    | -                    |  |
| Drain Height to Floor - in (mm)              | 4.3 (108)                     | -                    |  |
| Heat Input Power - Btu/hr (kW, Mj/hr.)       | -                             | 73,000 (21.4, 77.0)  |  |
| Gas Connection - in                          | -                             | 1/2 NPT              |  |
| Air Outlet - in (mm)                         | -                             | 8.0 (200) Elliptical |  |
| Airflow - cfm (l/sec)                        | -                             | 400 (190)            |  |
| Motor - HP (kW) Fan                          | -                             | 0.5 (0.4)            |  |
| Drive                                        | 1 (0.75)                      | 0.3 (0.2)            |  |
| Total # of Speeds                            | 9                             | -                    |  |
| Cylinder Speeds - RPM Gentle                 | 34 (0.4)                      | -                    |  |
| (Ğ-Force) Wash                               | 48 (0.8)                      | -                    |  |
| Distribution                                 | 86 (2.5)                      | -                    |  |
| Very Low                                     | 282 (27)                      | -                    |  |
| Low                                          | 485 (80)                      | -                    |  |
| Medium                                       | 542 (100)                     | -                    |  |
| High                                         | 606 (125)                     | -                    |  |
| Very High                                    | 664 (150)                     | -                    |  |
| Ultra High                                   | 766 (200)                     | -                    |  |
| Electrical Specs - amps X 200-240V/50/60/1/3 | 15                            | 10                   |  |
| Shipping Width                               | 34.5 (876)                    |                      |  |
| Dimensions<br>Approx in (mm)                 | 4                             | 47.0 (1194)          |  |
| Height                                       | 83.0 (2108)                   |                      |  |
| Net Weight - lb (kg)                         | 770 (349)                     |                      |  |
| Shipping Weight - lb (kg)                    |                               | 787 (357)            |  |
| Agency Approvals                             | <sub>c</sub> UL <sub>us</sub> | CSA                  |  |

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.